

# FORM RELEASE AGENTS

## MC-3000M

**DESCRIPTION:** Form release agent MC 3000M is used for lubricating of forms and formworks during producing low-porosity concrete items. The material used on the concrete form surfaces to prevent the concretes from sticking to the forms or formworks. Product provides easy setting and items' surface low-porosity and less irregularities and bugholes.



**APPLICATION:** Can be applied with brush or by pulverization.

### ADVANTAGES:

- Ensures positive separation of concrete and production pallet
- Provides god quality of item's external surfaces
- Reduces porosity on the external surfaces
- Ensures absence of oil spots on the painted surfaces
- Reduces costs for form release agents
- Compared with famous analogues

### TEMPERATURE RANGE:

- Application temperature + 5 °C + 80 °C
- Storage temperature - 40 °C до + 40 °C

**PACKAGE:** Steel barrels 200l

### Technical Sheet

**Appearance:** low-viscosity transparent oil fluid

**Color:** yellow

**Thickness:** 0,8 – 0,9

**Viscosity (20°C):** 10-13 g/sm<sup>3</sup>

**Consumption rate:** 0,03-0,035 kg/m<sup>2</sup>

**TC 2332-034-45540231-2010**

### PROJECTS:

- PARKON LLC , St-Petersburg (Russia)
- T-BETON LLC, Tosno (Russia)
- INGEOCOM, Moscow (Russia)